


# DCONNECT ALL-IN-ONE



**DConnect All-In-One** is the gateway designed to meet the diverse needs of the DTI market. The electronics are controlled by the ESP32-S3 microcontroller and can be used in two modes:

- **Gateway** from RS485 to Wi-Fi/LTE CAT1, NB, and CAT-M to DCloud (DTI cloud) or AWS.
- **Standalone**, a mode in which the board processes a series of signals and sends data to the cloud.

For both versions, it is possible to interface with devices connected via Bluetooth. The electronics offer several configurations, allowing connection to Wi-Fi only or to the mobile network in any geographic area.

## HIGHLIGHTS



OTA update



Bluetooth



Client Cloud



Web Server configuration



Ecomode for energy saving



GPIOs



GSM



RS232



RS485



WIFI

## TECHNICAL FEATURES


RS485 communication (Modbus)

ESP32-S3-WROOM-1-N16 processor

Bluetooth and Wi-Fi connectivity with integrated antenna

Wi-Fi frequency: 2.4 GHz 802.11 b/g/n

## TECHNICAL DRAWINGS



D530044300 - DCONNECT ALL-IN-ONE



SD CARD



STATUS LED

RS485B	RS485A	+VRS485	GND	+5V	EV OUT2	EV OUT1	PRESS	+5V	LIV REF	LVL	NTC	GND	VOLUM	GND	+VIN
1															16



e-mail: [info@dtindustry.com](mailto:info@dtindustry.com) sito: [www.dtindustry.com](http://www.dtindustry.com)